

INTERVAL TURF

Centaur has revolutionized indoor turf by fusion bonding a premium turf surface layer to a 5mm or 12mm vulcanized composition rubber base layer. The result is an ideal surface for footwork and functional training while providing cushion underfoot and sound isolating advantages.



PRODUCT & COLOR OPTIONS

Rolls:

6' x 35' roll; 17mm (12mm + 5mm) thick
6' x 25' roll; 24mm (12mm + 12mm) thick

Interlocking Tiles:

23" x 46" interlocking tile; 24mm thick

All options are available in Green, Black, Gray, and Blue

5mm BASE LAYER



FORCE REDUCTION 30.8%



ENERGY RESTITUTION 46.6%

12mm BASE LAYER



FORCE REDUCTION 47.1%



ENERGY RESTITUTION 41.0%

PRODUCT FEATURES

- Impact reduction
- No infill required
- Portable & easy to install (Interlocking Tiles)

APPLICATIONS

- Indoor functional training
- Speed and agility areas
- Home gyms

PHYSICAL DATA

Performance Criteria Density

Force Reduction

Energy Restitution

Vertical Deformation

G-Max

Tufted Pile Height

Pill Test / Flammability

Coefficient of Friction

Test Method

Deltec

Deltec

Deltec

Clegg

ASTM D2859

ASTM D2047

Results

5mm | **12mm**

30.8% | 47.1%

46.6% | 41.0%

3.8mm | 4.9mm

192 | 84

0.47" | 0.47"

Pass | Pass

0.87_(dry) | 0.87_(dry)

INSTALLATION FAST FACTS

- Rolls may be installed over concrete, approved Portland-based patching and leveling materials and wood
- Interlocking Tiles may be installed over wood, concrete subfloors or firmly adhered resilient flooring such as vinyl, linoleum, laminate, ceramic tile, and wood