

STRIVE

Strive features a 2.5mm vulcanized composition rubber (VCR) surface layer factory fusion bonded to a 12mm VCR base layer. Strive is a high performance, durable surface that provides exceptional ergonomic benefits to the user. This product is ideal for free weights and functional training applications.



PRODUCT & COLOR OPTIONS

Rolls:

14.5mm x 4' wide rolls

Interlocking Tiles:

23" x 23" interlocking tile; 14.5mm thick

Available in 12 colors



FORCE REDUCTION 35.4%



ENERGY RESTITUTION 53.7%

PRODUCT FEATURES

- Durable
- Sustainable
- Ease of maintenance
- Slip-resistant
- Interlocking tiles are easy to install

APPLICATIONS

- Multi-purpose Areas
- Running/walking Tracks
- Physical Therapy
- Fitness Spaces
- Retail

PHYSICAL DATA

Performance Criteria Density

Static Load Limit
Coefficient of Friction
FloorScore
Abrasion Resistance
Pill Test
Standard Vertical Deformation
Surface Effect Slip Resistance
Ball Rebound
Force Reduction
Impact Insulation Class IIC*
Delta IIC*

Test Method

ASTM F970
ASTM D2047
CA 01350
ASTM D3389
ASTM D2859
ASTM F2772
ASTM F2772
ASTM F2772
ASTM F2772
ASTM E492
ASTM E2179

Typical Results

0.009" (@250psi)
>0.9
Certified
<1g 1,000 cycles
Pass
2.66mm
Pass
98.8%
35.7%
58
27

*Tested on a 6" concrete slab with no ceiling.