

# THRIVE

Featuring a 2.5mm vulcanized composition rubber (VCR) surface layer factory fusion bonded to a 5mm VCR base layer, Thrive is an ergonomic surface that is ideal for functional training areas, cardio spaces, light weights, and general fitness spaces.



## PRODUCT & COLOR OPTIONS

### Rolls:

7.5mm x 4' wide rolls

Available in 12 colors



**FORCE REDUCTION** 12.6%



**ENERGY RESTITUTION** 66.8%

## PRODUCT FEATURES

- Durable
- Sustainable
- Ease of maintenance
- Slip-resistant
- Interlocking tiles are easy to install

## APPLICATIONS

- Multi-purpose Areas
- Physical Therapy
- Fitness Spaces
- Retail
- Home Gyms

## PHYSICAL DATA

### Performance Criteria Density

Static Load Limit  
Coefficient of Friction  
FloorScore  
Abrasion Resistance  
Pill Test  
Standard Vertical Deformation  
Surface Effect Slip Resistance  
Ball Rebound  
Force Reduction  
Impact Insulation Class IIC\*  
Delta IIC\*

### Test Method

ASTM F970  
ASTM D2047  
CA 01350  
ASTM D3389  
ASTM D2859  
ASTM F2772  
ASTM F2772  
ASTM F2772  
ASTM F2772  
ASTM E492  
ASTM E2179

### Typical Results

0.004" (@250psi)  
>0.9  
Certified  
<1g 1,000 cycles  
Pass  
.73mm  
Pass  
99.7%  
12.6%  
54  
24

\*Tested on a 6" concrete slab with no ceiling.